

Technical Specifications

Model	ULTIMATE 200
Max. Depth of Tray	70 mm
Max. Width of Film	500 mm
Max. Diameter of Film	220 mm
Packing Speed	2-3 cycle/min
Power Supply	230V/50Hz
Net Weight	110 kg
Machine Dimensions W x L x H (mm)	540x700x750 mm

* The manufacturer reserves the right to make changes in machine designs. The actual machine design may differ from the images in the brochure.



We protect your food
for sustainable freshness

CE EAC
Turkey
Discover
the potential

Distributor / Dealer
B.I.S. Business Intelligence Solutions
Sahrayıcedit Mah. İnönü Cad.
No: 57/2 Kadıköy / İstanbul / TURKEY
M. +33 6 72 33 73 05
contact@bismc.com



ULTIMATE[®]
PACKAGING EXPERIENCE

**VACUUM & GAS
TRAY
SEALERS**



Longer Shelf Life with ULTIMATE 200 MAP TRAY SEALER

Ultimate 200 MAP Tray Sealer has been designed for small and medium-size food processing. Semi-automatic system allows you to vacuum, gas, seal, and cut using a wide variety of trays in various shapes and sizes. The operator, during each cycle, is only required to load the drawer of the machine. Ideal for low-volume operations, this space-saving unit will deliver the same quality packages as larger more automated systems. Its unique stainless steel robust construction design is ideal for the food industry. Ultimate 200 MAP Tray Sealer is the right choice when launching new product lines, developing new packaging ideas or when you just need to safely package your current production.

Keeps fresh and cooked food products not only packaged but also fresh. Food gas in suitable feature for this purpose can be used and can be adjusted with high precision. It's widely applicable for the package of raw and cooked meat, poultry, fast food, soy products, sea food, dairy products, fruit and vegetable, rice and food.




STANDARD FEATURES

- Large format 325x265 mm sealing area
- Gas Flushing & Vacuum feature for applications requiring modified atmospheres (MAP)
- Automatic film seal & trim and scrap rewind
- Optional clear or random printed top film capability
- Changeable mould system
- Custom mould sizes and features quoted on request
- User friendly Touch Screen LCD control panel
- Main power/Heater OFF/ON switch
- Electronic temperature control
- Safety plate for operator
- Quick change tooling feature
- No need for air compressor for film sealing and cutting
- Without vibration working feature
- Precision film cutting system
- High-efficiency vacuum pump
- Inert gas injection system
- Casters (*only available for stand alone version)
- AISI 304 stainless steel construction
- CE certified



TRAY OPTIONS



325 x 265 mm



227 x 178 mm



190 x 144 mm



Ø 220

